



## SINTAS INDUSTRIAL PAINT

Our product, which is alkyd essentialized and air dried paint, is specially formulated for topcoat paintings. It has ultra adhesion to nominative metallic surfaces and flexibility.

<b>Product</b>	<b>Sintas Industrial Paint</b>
<b>Color</b>	<b>All colors are available.</b>
<b>Application Area</b>	<b>Steel, galvanised steel and non-ferrous metallic surfaces</b>
<b>Density (20°C, g/cm<sup>3</sup>)</b>	<b>0.9 – 1.20 (according to color)</b>
<b>Solid (% weight)</b>	<b>58 - 64 (according to color)</b>
<b>Application Viscosity (DIN CUP 4/20°C)</b>	<b>18 - 20 sec</b>
<b>Drying time (20 °C)</b>	
<b>Powder Drying</b>	<b>10-15 minutes</b>
<b>Touch Drying</b>	<b>25 – 30 minutes</b>
<b>Montage Drying</b>	<b>1 hour</b>
<b>Thinning Ratio</b>	<b>%20 – 25</b>
<b>Application Types</b>	<b>Spraying, immersion, brush</b>
<b>Dry Film Thickness</b>	<b>30 – 35 microns (single coat)</b>
<b>Application Area</b>	<b>8-10 m<sup>2</sup> area with 1 liter Sintas Industrial Paint (single coat)</b>
<b>Application Method</b>	<b>Purify surfaces from grease, rust or dust. It should be applied by spraying. In case of changing application type, please contact with our technical service.</b>
<b>Remarks</b>	<b>During the application take care air and climate conditions.</b>
<b>Shelf Life</b>	<b>Unopened package can be stored at least 1 year under room temperature.</b>
<b>Health and Security Information</b>	<b>Look at labels on package. Users should destroy to the wastages according to health and security standards.</b>
<b>Symbol</b>	<b>F</b>
<b>Risk Warning</b>	<b>10</b>
<b>Security Warning</b>	<b>6-20/21-23-38</b>
<b>Packing</b>	<b>18 kg, 2.5 lt and 0.75 lt packages</b>

In case of using on primer, it provides high water resistance. It is thinned with Sintas Industrial Thinner and maintains glossiness.

